



- 115mm (4.5in) Interleaved Sandwich Voice coil (ISV)
- Weather protected cone and plates
- Great heat dissipation capability
- Ultra linear suspension system
- Neo motor for high power and very efficient thermal exchange
- Single demodulating ring (SDR) for distortion reduction and maximum SPL

The 15NLW4500 is a 15" extended low frequency loudspeaker, designed for use in vented, bandpass or even horn loaded enclosures. The loudspeaker is designed to withstand high power levels without damage while providing clean and undistorted LF reproduction at a very high SPL. For optimum results we recommend amplifiers able to deliver 3000 Watt program power. The 15NLW4500 features a unique motor featuring a high grade Neo magnet assembly in a structure optimized for thermal and magnetic efficiency. 15NLW4500 features include a large displacement suspension system which, in conjunction with a composite reinforced, straight ribbed cone and the Eighteen Sound proprietary SDR technology, allows an undistorted ultra-linear piston action and provides full mechanical control across the entire working range. The 115mm (4.5 in) state-of-the-art voice-coil utilizing Interleaved Sandwich Voice coil (ISV) technology, provides high levels of thermal stability and durability. The ISV technology achieves a balanced linear motor unit exerting an exceptionally high force factor.



SPECIFICATIONS

| | |
|--|------------------|
| Nominal Impedance | 8 Ω |
| Minimum Impedance | 6.7 Ω |
| Nominal Power Handling ¹ | 1500 W |
| Continuous Power Handling ² | 3000 W |
| Sensitivity ³ | 96.3 dB |
| Frequency Range | 40 - 1000 Hz |
| Voice Coil Diameter | 115 mm (4.53 in) |

DESIGN

| | |
|-----------------------|--|
| Recommended Enclosure | 50.0 dm ³ (1.77 ft ³) |
| Recommended Tuning | 45 Hz |

PARAMETERS⁴

| | |
|---------------------|---|
| Resonance Frequency | 35 Hz |
| Re | 5.4 Ω |
| Qes | 0.27 |
| Qms | 7.8 |
| Qts | 0.26 |
| Vas | 111.0 dm ³ (3.92 ft ³) |
| Sd | 881.0 cm ² (136.56 in ²) |
| η _o | 1.7 % |
| X _{max} | 14.5 mm |
| X _{var} | 12.0 mm |
| M _{ms} | 201.0 g |
| Bl | 29.7 T·xm |
| Le | 1.62 mH |
| EBP | 129 Hz |

MOUNTING AND SHIPPING INFO

| | |
|-----------------------------|---------------------|
| Overall Diameter | 393 mm (15.47 in) |
| Bolt Circle Diameter | 371 mm (14.61 in) |
| Baffle Cutout Diameter | 356.0 mm (14.02 in) |
| Depth | 199 mm (7.83 in) |
| Flange and Gasket Thickness | 15 mm (0.61 in) |
| Net Weight | 11.4 kg (25.13 lb) |
| Shipping Weight | 12.6 kg (27.78 lb) |

1. 2 hours test made with continuous pink noise signal within the range Fs-10Fs. Power calculated on rated minimum impedance. Loudspeaker in free air.
2. Power on Continuous Program is defined as 3 dB greater than the Nominal rating.
3. Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.
4. Thiele-Small parameters are measured after a high level 20 Hz sine wave preconditioning test.